

LF/HF/NFC ABS Keyfob

RFID keyfob contain an antenna that receives and transmits the RFID signal. They are used in a wide variety of applications. They are effective for personnel tracking, bank, hotel key card , Student/Campus Card, Leisure card, intelligent parking management, access control, time and attendance, logical access loyalty programs, as well as near field communication (NFC) applications.



Technical Data Sheet:

| | |
|-----------------------|---|
| Model | RC4010 |
| Material | ABS |
| Dimensions | 35 x 35 x 5mm |
| RFID Standard | ISO 7805 / ISO14443A / ISO 15693 |
| Working Frequency | 125KHz/ 13.56MHz |
| Chip Available | LF:TK4100, EM4200, EM4305, T5577 etc. HF:MF S50, MF S70, MF Ultralight, MF Ultralight C, FM1108, ICODE SLI-L, ICODE SLI, ICODE SLI-S, DESFire EV1 4K, DESFire EV1 8K, etc. NFC: Ntag213, Ntag215, Ntag216 |
| Reading Range | 1-10CM |
| Waterproof | IP 65 |
| Memory | LF: 64-2568 bits, HF: 512bits-8k |
| Data Storage | > 10 years |
| Re-write | 100,000 times |
| Operating Temperature | -40℃ ~ 80℃ |
| Storage Temperature | -40℃ ~ 80℃ |
| Color | optional |
| Option | Numbering, Encoding, Printing Logo, etc. |

Application:

- Access Control
- Intelligent Parking Management
- Vehicle Management
- Hotel Key Card
- Loyalty & Member Card
- Inventory Management

