




Vibe 70 x 14 mm M830

The Vibe from RICHRFID is a versatile, high-performance dry inlay designed for apparel and fashion, library and archives, automotive, and warehouse logistics applications. It performs exceptionally well on packaging materials such as corrugated cardboard and plastic transport containers.

The product complies with EPCglobal Class 1 Gen 2 and is manufactured under ISO 9001 quality management and ISO 14001 environmental management standards, ensuring reliable, industry-grade performance for diverse use cases.

Equipped with the Impinj M830 IC, it offers improved read/write sensitivity compared with the M700 series, enabling faster and more accurate bulk reading performance. The Impinj IC is compatible with the global GS1 UHF Gen2v2 standard, standardized by ISO/IEC as 18000-63.

When Impinj Protected Mode is enabled, the converted label can help protect item data privacy, making it suitable for highvalue products, authenticity verification, and applications requiring enhanced privacy protection.

Designed with a 70 x 14 mm dry inlay for conversion into a compact 73 x 20 mm RFID label, it provides sufficient area for QR codes, serial numbers, and other visible data, making it ideal for stacked packaging applications.

Overview


Frequency Band
UHF 860-960 MHz

Chip Type
Impinj M830

Dimensions
70 x 14 mm / 2.76 x 0.55 in

Air Interface Protocol
ISO/IEC 18000-63 Type C


Application
Retail & Apparel
Asset tracking
Smart packaging
Authentication




Technical Features

Chip Type	Impinj M830	
EPC	128 bits	
User	NA	
TID	96 bits	
Model	—	RC5128
Delivery Format	Dry Inlay	Label
Die-Cut Dimension	—	73 x 20 mm / 2.87 x 0.79 in
Inlay Substrate	50 um PET	50 um PET
Face Material	—	Coated Paper
Adhesive	—	Hot Melt
Standard Pitch	22.225 mm / 0.875 in	22.225 mm / 0.875 in
Web Width	87 mm / 3.43 in	85 mm / 3.35 in
Core inner Diameter	76.2 mm / 3.0 in	76.2 mm / 3.0 in
Operating Temperature	-40°C to 85°C / -40°F to 185°F	
Storage Condition	20±5°C, 50±10% RH, Store away from sunlight	
Installation	—	Adhesive on clean & dry surface
Customization	Encoding, Designing, etc.	Printing, Encoding, Designing, etc.
Package	10,000 pcs / roll, 4 rolls / box	2,500 pcs / roll, 4 rolls / box
Application	Non-metal	

Read Range(2W ERP)



Radiation Pattern



PS: The performance is theoretical values in the lab and the actual effect depends on the specific applications.

RICHRFID

Web: <https://www.richrfid.com> E-mail: info@richrfid.com
 Shenzhen | Hong Kong | Singapore | Seoul | Tokyo | Paris



DISCLAIMER

All specifications are indicative and results may vary. Each user bears full responsibility for making its own determination as to the suitability of RICHRFID products, materials, services, recommendations, or advice for its own particular use.

For intended use only. Not to be repurposed or used for other applications without prior written permission from the manufacturer.

@2026 RICHRFID. All rights reserved.